

Pos	Material	Comment	breaking strength bended(daN)	Number of lines	Level				
					0	1	2	3	4
a1	DC60		50,2	2			100	100	
a2	DC60		50,2	2			100	100	
a3	DC60		50,2	2			100	100	
a4	DC60		50,2	2			100	100	
a5	DC60		50,2	2			100	100	
a6	DC60		50,2	2			100	100	
a7	DC60		50,2	2			100	100	
a8	DC60		50,2	2			100	100	
a9	DC60		50,2	2			100	100	
a10	DC60		50,2	2			100	100	
a11	DC60		50,2	2			100	100	
a12	DC60		50,2	2			100	100	
A1	PPSLS125		89,5	2		179			
A2	PPSLS125		89,5	2		179			
A3	PPSLS125		89,5	2		179			
A4	PPSLS125		89,5	2		179			
A5	PPSLS125		89,5	2		179			
A6	PPSLS125		89,5	2		179			
AI	PPSLS180	Loop Cover top side	137,8	2	276				
AII	PPSLS180	Loop Cover top side	137,8	2	276				
AIII	PPSLS180	Loop Cover top side	137,8	2	276				
b1	DC60		50,2	2			100	100	
b2	DC60		50,2	2			100	100	
b3	DC60		50,2	2			100	100	
b4	DC60		50,2	2			100	100	
b5	DC60		50,2	2			100	100	
b6	DC60		50,2	2			100	100	
b7	DC60		50,2	2			100	100	
b8	DC60		50,2	2			100	100	
b9	DC60		50,2	2			100	100	
b10	DC60		50,2	2			100	100	
b11	DC60		50,2	2			100	100	
b12	DC60		50,2	2			100	100	
B1	PPSLS125		89,5	2		179			
B2	PPSLS125		89,5	2		179			
B3	PPSLS125		89,5	2		179			
B4	PPSLS125		89,5	2		179			
B5	PPSLS125		89,5	2		179			
B6	PPSLS125		89,5	2		179			
BI	PPSLS180	Loop Cover top side	137,8	2	276				
BII	PPSLS180	Loop Cover top side	137,8	2	276				
BIII	PPSLS180	Loop Cover top side	137,8	2	276				
c1	DC60		50,2	2				100	
c2	DC60		50,2	2				100	
c3	DC60		50,2	2				100	
c4	DC60		50,2	2				100	
c5	DC60		50,2	2				100	
c6	DC60		50,2	2				100	

c7	DC60		50,2	2		100					
c8	DC60		50,2	2		100					
c9	DC60		50,2	2		100					
c10	DC60		50,2	2		100					
c11	DC60		50,2	2		100					
c12	DC60		50,2	2		100					
C1	DC60		50,2	2	100	100					
C2	DC60		50,2	2	100	100					
C3	DC60		50,2	2	100	100					
C4	DC60		50,2	2	100	100					
C5	DC60		50,2	2	100	100					
C6	DC60		50,2	2	100	100					
C7	PPSLS125		89,5	2	179						
C8	PPSLS125		89,5	2	179						
CM1	PPSLS125		89,5	2	179						
CM2	PPSLS125		89,5	2	179						
CM3	PPSLS125		89,5	2	179						
CM4	PPSLS125		89,5	2	179						
CI	PPSLS180	Loop Cover top side	137,8	2	276						
CII	PPSLS180	Loop Cover top side	137,8	2	276						
CIII	PPSLS180	Loop Cover top side	137,8	2	276						
d1	DC60		50,2	2		100					
d2	DC60		50,2	2		100					
d3	DC60		50,2	2		100					
d4	DC60		50,2	2		100					
d5	DC60		50,2	2		100					
d6	DC60		50,2	2		100					
d7	DC60		50,2	2		100					
d8	DC60		50,2	2		100					
D1	DC60		50,2	2	100	100					
D2	DC60		50,2	2	100	100					
s1	DC60		50,2	2	100	100					
s2	DC60		50,2	2		100					
s3	DC60		50,2	2		100					
s4	DC60		50,2	2	100	100					
s5	DC60		50,2	2		100					
s6	DC60		50,2	2		100					
s7	DC60		50,2	2		100					
S1	PPSLS65		46,4	2	93						
S2	PPSLS65		46,4	2		93					
S3	PPSLS65		46,4	2		93					
SM1	PPSLS65		46,4	2	93						
S	PPSLS125		89,5	2	179						
Marquartstein, am 01.02.2021 			Fbreak Level				2659	3408	3598	5924	
			Wmax Level				190	243	257	423	daN
							>135	>135	>135	>135	kg

Pos	Material	Comment	breaking strength bended	Number of lines	Level				
					0	1	2	3	4
br1	DC60	mit Hike2 Bremsgriff	50,2	2					100
br2	DC60		50,2	2					100
br3	DC60		50,2	2					100
br4	DC60		50,2	2					100
br5	DC60		50,2	2					100
br6	DC60		50,2	2					100
br7	DC60		50,2	2					100
br8	DC60		50,2	2					100
br9	DC60		50,2	2					100
br10	DC60		50,2	2					100
br11	DC60		50,2	2					100
br12	DC60		50,2	2					100
BR1	PPSLS65		46,4	2				93	
BR2	PPSLS65		46,4	2				93	
BR3	PPSLS65		46,4	2				93	
BR4	PPSLS65		46,4	2				93	
BR5	PPSLS65		46,4	2				93	
BR6	PPSLS65		46,4	2				93	
BRI	PPSLS65		46,4	2			93		
BRII	PPSLS65		46,4	2			93		
BRIII	PPSLS65	46,4	2			93			
Brmain	DFLP200/32		85,9	2	172				
Brmain2	PPSL125		89,5	2		179			
			Fbreak Level		172	179	278	557	1205
			Wmax Level		172	179	278	557	1205
					>150	>150	>150	>150	>150

daN

kg

daN

kg

