

G I N

Date:	23.11.2013
-------	------------

4[illegible][illegible]

X
X
X

B

[illegible]

			x
			x
			x
			x
		x	x
		x	x
	x	x	x
		x	x
		x	x
	x	x	x
		x	x
		x	x
	x	x	x
		x	x
		x	x

[illegible][illegible]

X			
X			
X			
X			

[illegible][illegible]

CC

10

1

1

1

11

1

DD

D3		2								
D4		2								
D5		2								
D6		2								
D7		2								
D8		2								
D9		2								
D10		2								
Main										
DI		2								
DII		2								
DIII		2								
DIV		2								

Upper	E									
e1		2								
e2		2								
e3		2								
e4		2								
e5		2								
e6		2								
e7		2								
e8		2								
e9		2								
e10		2								
e11		2								
e12		2								
e13		2								
e14		2								
e15		2								
e16		2								
e17		2								
e18		2								
e19		2								
e20		2								
e21		2								
e22		2								
e23		2								
e24		2								
e25		2								

High mid										
E1		2								
E2		2								
E3		2								
E4		2								
E5		2								
E6		2								
E7		2								
E8		2								
E9		2								
E10		2								
E11		2								
E12		2								
E13		2								
E14		2								
E15		2								

Low mid										
E1		2								
E2		2								
E3		2								
E4		2								
E5		2								
E6		2								
E7		2								
E8		2								
E9		2								
E10		2								

Main										
EI		2								
EII		2								
EIII		2								
EIV		2								

Fbreak L1	Fbreak L2	Fbreak L3	Fbreak L4
3346,4	3157,8	4568,8	5286,4

Enter the max Load [kg]
120,0

Wmax L1	Wmax L2	Wmax L3	Wmax L4
243,7	229,9	332,7	384,9

	Brake										
level 1	8000/U-190	140,2	2	280,4						x	
level 2	8000/U-090	56,7	6		340,2					x	
level 3	8000/U-070	32,9	12			394,8				x	
level 4	8000/U-050	28,4	24				681,6				x

Fbreak L1	Fbreak L2	Fbreak L3	Fbreak L4
280,4	340,2	394,8	681,6

Enter the strength of the connection between the handle and the first level of line [daN]
80