

<i>Light Performance Intermediate certification EN-A / EN-B</i>	Aravis 17 (XS)	Aravis 19 (XS)	Aravis 21 (S)	Aravis 23 (M)	Aravis 25 (L)	Aravis 28 (XL)
Zoom flat [%]	0,86	0,91	0,955	1,00	1,055	1,11
Area flat [m ²]	16,83	18,85	20,76	22,76	25,33	28,04
Area projected [m ²]	14,85	16,63	18,31	20,08	22,35	24,74
Span flat [m]	9,32	9,86	10,35	10,84	11,44	12,03
Aspect ratio flat	5,16	5,16	5,16	5,16	5,16	5,16
Root cord [m]	2,21	2,34	2,45	2,57	2,71	2,85
Cells	50	50	50	50	50	50
Weight [kg]	2,4	2,6	2,8	3,1	3,3	3,6
Weight range [kg] * EN A	-	-	50-80	60-93	75-105	85-115
Min.speed [km/h]	23-25	23-25	23-25	23-25	23-25	23-25
Max.speed [km/h]	37-39	37-39	37-39	37-39	37-39	37-39
Top speed (accelerator) [km/h]	48-50	48-50	48-50	48-50	48-50	48-50
Glide ratio	+10	+10	+10	+10	+10	+10
Min. Sink rate [m/s]	1,05	1,05	1,05	1,05	1,05	1,05
Area projected [m ²]	14,85	16,53	18,31	20,08	22,35	24,74
Span projected [m ²]	7,71	8,15	8,56	8,96	9,45	9,95
Aspect ratio projected	4	4	4	4	4	4
Middle line length	5,51	5,8	6,06	6,32	6,64	6,96
Total line length	156,1	174,8	192,5	211	234,9	260