



Stückliste

Datum: 22.12.2022

Version: 1.0



**SWING Flugsportgeräte
GmbH**

An der Leiten 4
82290 Landsberied

Bezeichnung	Bestell Nr.	Werkstoff	Abmessung	Oberfläche	Hersteller
Fangleinenschlösser	MRDI03.0 12.30	Inox	ø 3,0 mm	Edelstahl	Techtex
Rahmenring	DRI03.0 8.13	Inox	ø 3,0 mm	Edelstahl	Techtex
Fangleinen (Stamm)	8001-230 / 8001-190 / 7343-140	Aramid	ø 1,4 mm / 1,2 mm / 1,3 mm	unummantelt / ummantelt	Edelrid
Fangleinen (1.Gabel)	8001-190 / 8001-130	Aramid	ø 1,2 mm / 1,0 mm	unummantelt	Edelrid
Fangleinen (2.Gabel)	DC 100 / DC 60	Dyneema	ø 0,8 mm / 0,6 mm	unummantelt	Liros
Tuch Obersegel	Skytex 38 / STA 15 / STA 10	Nylon	38 g/m ² - 31 g/m ² - 28 g/m ²	beschichtet	Porcher Sport / Techfiber Services, Inc Japan
Tuch Untersegel	STA 10	Nylon	28 g/m ²	beschichtet	Techfiber Services, Inc Japan
Tuch Profile	9017 E29 / 70000 E91	Nylon	38 g/m ² - 27 g/m ²	beschichtet	Porcher Sport
Gurtband	12mm BLK	Aramid / Polyester	12 mm / 2 mm		Cousin
Profilverstärkung	Support rod	Nitinol / Nylon	ø 0,8 mm / 0,6 mm, tubecover		Techtex
Bremsleinen	DFLS 200 / 8001-090 / -050	Dyneema / Aramid	ø 2,0 mm / 0,9 mm / 0,5 mm	ummantelt / unummantelt	Liros / Edelrid



Date: 22.12.2022

Parts list

Version: 1.0

**SWING Flugsportgeräte
GmbH**

An der Leiten 4
82290 Landsberied

Description	Article Code	Material	Dimensions	Surface	Manufacturer
quick links	MRDI03.0 12.30	Inox	ø 3,0 mm	Stainless steel	Techtex
D-ring	DRI03.0 8.13	Inox	ø 3,0 mm	Stainless steel	Techtex
Rigging line (Main)	8001-230 / 8001-190 / 7343-140	Aramid	ø 1,4 mm / 1,2 mm / 1,3 mm	uncovered	Edelrid
Rigging line (intermediate)	8001-190 / 8001-130	Aramid	ø 1,2 mm / 1,0 mm	uncovered	Edelrid
Rigging line (top)	DC 100 / DC 60	Dyneema	ø 0,8 mm / 0,6 mm	uncovered	Liros
Fabric topsail	Skytex 38 / STA 15 / STA 10	Nylon	38 g/m ² - 31 g/m ² - 28 g/m ²	coated	Porcher Sport / Techfiber Services, Inc Japan
Fabric bottomsail	STA 10	Nylon	28 g/m ²	coated	Techfiber Services, Inc Japan
Fabric ribs	9017 E29 / 70000 E91	Nylon	38 g/m ² - 27 g/m ²	coated	Porcher Sport
Riser webbing	12mm BLK	Aramid / Polyester	12 mm / 2 mm		Cousin
Profil support	Support rod	Nitinol / Nylon	ø 0,8 mm / 0,6 mm, tubecover		Techtex
Brake line	DFLS 200 / 8001-090 / -050	Dyneema / Aramid	ø 2,0 mm / 0,9 mm / 0,5 mm	covered / uncovered	Liros / Edelrid