

Version: 2.2 (11.05.2022)

 **GIN**

[illegible][illegible]

X			
X			
X			

[illegible]

b9	8001-050	28,4	2			56,8
b10	8001-050	28,4	2			56,8
b11	8001-050	28,4	2			56,8
b12	8001-050	28,4	2			56,8
b13	8001-050	28,4	2			56,8
b14	8001-050	28,4	2			56,8
b15	8001-050	28,4	2		56,8	56,8
b16	8001-050	28,4	2	56,8	56,8	56,8
b17	8001-050	28,4	2		56,8	56,8
b18	8001-050	28,4	2		56,8	56,8

			X
			X
			X
			X
			X
			X
		X	X
	X	X	X
		X	X
		X	X

H/Mid

B1	8001-070	32,9	2		65,8
B2	8001-070	32,9	2		65,8
B3	8001-070	32,9	2		65,8

		X	
		X	
		X	

Mid

B1	8001-070	32,9	2	65,8	
B2	8001-070	32,9	2	65,8	
B3	8001-070	32,9	2	65,8	
B4	8001-070	32,9	2	65,8	
B5	live-threatening		2	#NV	
B6	8001-070	32,9	2	65,8	
B7	8001-050	28,4	2	56,8	

	X		
	X		
	X		
	X		
	X		
	X		
	X		
	X		

Main

BI	8001-230	168,0	2	336	
BII	8001-230	168,0	2	336	
BIII	8001-130	82,3	2	164,6	
STB	8001-090	56,7	2	113,4	

X			
X			
X			
X			

Upper

c1	8001-050	28,4	2		56,8	56,8
c2	8001-050	28,4	2		56,8	56,8
c3	8001-050	28,4	2		56,8	56,8
c4	8001-050	28,4	2		56,8	56,8

		X	X
		X	X
		X	X
		X	X

B

C

c5	8001-050	28,4	2			56,8	56,8
c6	8001-050	28,4	2			56,8	56,8
c7	8001-050	28,4	2			56,8	56,8
c8	8001-050	28,4	2			56,8	56,8

		X	X
		X	X
		X	X
		X	X

Mid							
C1	8001-050	28,4	2		56,8		
C2	8001-050						
C3	8001-050						
C4	8001-050						

	X		

C

Enter
the max
Load
[kg]
125,0

Fbreak L1	Fbreak L2	Fbreak L3	Fbreak L4
2244,8	#NV	2870	3288
Wmax L1	Wmax L2	Wmax L3	Wmax L4
163,4	#NV	209,0	239,4

Brake											
Handle / Level 1	TGL220-Handle1	93,8									
Level 1	TGL 220	117,0	2	234				X			
Level 2	8001-070	32,9	6		197,4				X		
Level 3	8001-050	28,4	12			340,8				X	
Level 4	8001-050	28,4	24				681,6				X

Fbreak handle/L1	Fbreak L1	Fbreak L2	Fbreak L3	Fbreak L4
93,8	234	197,4	340,8	681,6