

Pos	Material	Comment	breaking strength bended(daN)	Numbe r of lines	Level				
					0	1	2	3	4
a1a	8001-90		61,2	2				122,4	
a2a	8001-90		61,2	2				122,4	
a3a	8001-90		61,2	2				122,4	
a4a	8001-90		61,2	2				122,4	
a5a	8001-70		31,2	2				62,4	
a6a	8001-70		31,2	2				62,4	
a7a	8001-70		31,2	2				62,4	
a8a	8001-70		31,2	2				62,4	
a9	8001-50		27,5	2			55,0	55,0	
a10	8001-50		27,5	2			55,0	55,0	
a11	8001-50		27,5	2		55,0	55,0	55,0	
amu1	8001-130		63,8	2				127,6	
amu2	8001-90		61,2	2				122,4	
amu3	8001-90		61,2	2				122,4	
amu4	8001-130		63,8	2				127,6	
amu5	8001-90		61,2	2				122,4	
amu6	8001-90		61,2	2				122,4	
amu7	8001-70		31,2	2				62,4	
amu8	8001-90		61,2	2				122,4	
am1	8001-190		125,7	2			251,4		
am2	8001-190		125,7	2			251,4		
am3	8001-190		125,7	2			251,4		
am4	8001-130		63,8	2			127,6		
am5	8001-90		61,2	2			122,4		
as1	8001-340		247,3	2		494,6			
as2	8001-340		247,3	2		494,6			
as3	8001-130		63,8	2		127,6			
a1b	8001-90		61,2	2				122,4	
a2b	8001-90		61,2	2				122,4	
a3b	8001-90		61,2	2				122,4	
a4b	8001-90		61,2	2				122,4	
a5b	8001-70		31,2	2				62,4	
a6b	8001-70		31,2	2				62,4	
a7b	8001-70		31,2	2				62,4	
a8b	8001-70		31,2	2				62,4	
b1a	8001-50		27,5	2				55,0	
b2a	8001-50		27,5	2				55,0	
b3a	8001-50		27,5	2				55,0	
b4a	8001-50		27,5	2				55,0	
b5a	8001-50		27,5	2				55,0	
b6a	8001-50		27,5	2				55,0	
b7a	8001-50		27,5	2				55,0	
b8a	8001-50		27,5	2				55,0	
b9	8001-50		27,5	2				55,0	
b10	8001-50		27,5	2			55,0	55,0	
b11	8001-50		27,5	2		55,0	55,0	55,0	
bmu1	8001-70		31,2	2				62,4	
bmu2	8001-50		27,5	2				55,0	
bmu3	8001-50		27,5	2				55,0	
bmu4	8001-70		31,2	2				62,4	
bmu5	8001-50		27,5	2				55,0	
bmu6	8001-50		27,5	2				55,0	
bmu7	8001-50		27,5	2				55,0	
bmu8	8001-50		27,5	2				55,0	
bm1	8001-90		61,2	2			122,4		
bm2	8001-90		61,2	2			122,4		
bm3	8001-90		61,2	2			122,4		
bm4	8001-90		61,2	2			122,4		
bm5	8001-50		27,5	2			55,0		
bs1	8001-190		125,7	2		251,4			
bs2	8001-130		63,8	2		127,6			
bs3	8001-50		27,5	2		55,0			
b1b	8001-50		27,5	2				55,0	
b2b	8001-50		27,5	2				55,0	
b3b	8001-50		27,5	2				55,0	
b4b	8001-50		27,5	2				55,0	
b5b	8001-50		27,5	2				55,0	
b6b	8001-50		27,5	2				55,0	
b7b	8001-50		27,5	2				55,0	
b8b	8001-50		27,5	2				55,0	
a12a	9200-30		30,6	2				61,2	0,0
a12b	9200-30		30,6	2				61,2	0,0
a13a	9200-30		30,6	2				61,2	0,0
a13b	9200-30		30,6	2				61,2	0,0
a14a	9200-30		30,6	2				61,2	0,0
a14b	9200-30		30,6	2				61,2	0,0
am6	9200-30		30,6	2			61,2		
am7	9200-30		30,6	2			61,2		
as4	8001-50		27,5	2		55,0			
Fbreak Level					1606	1781	2027	2688	
Wmax Level					115	127	145	192	daN

DC60		0,6	Dyneema	n/a	66,3
DC35		0,4	Dyneema	n/a	35,9
8001-50	MagixPro-050	0,5	Aramid	n/a	27,5
8001-70	MagixPro-070	0,7	Aramid	n/a	31,2
8001-90	MagixPro-090	0,8	Aramid	n/a	61,2
8001-190	MagixPro-190	1,2	Aramid	n/a	125,7
8001-230	MagixPro-230	1,3	Aramid	n/a	136,8
PPSL-200		1,4	Dyneema	Polyester	150,0
PPSL-65		0,8	Dyneema	Polyester	49,4
DSL-70		1,0	Dyneema	Polyester	69,9
PPSL-120		1,2	Dyneema	Polyester	97,8
PPSL-125		1,2	Dyneema	Polyester	113,75
PPSL-160		1,4	Dyneema	Polyester	123,9
PPSL-180		1,3	Dyneema	Polyester	160,3
DFLP200/32		1,9	Dyneema	Polyester	91,5
8001-340		1,7	Technora	n/a	247,3
8001-130		1,0	Technora	n/a	63,8
8001-470			Technora	n/a	279,8
9200-30					30,6

Pos	Material	Comment	breaking strength bended	Numbe r of lines	Level				
					0	1	2	3	4
br1	9200-30		30,6	2					61,2
br2	9200-30		30,6	2					61,2
br3	9200-30		30,6	2					61,2
br4	9200-30		30,6	2					61,2
br5	9200-30		30,6	2					61,2
br6	9200-30		30,6	2					61,2
br7	9200-30		30,6	2					61,2
br8	9200-30		30,6	2					61,2
br9	9200-30		30,6	2					61,2
br10	9200-30		30,6	2					61,2
br11	9200-30		30,6	2					61,2
br12	9200-30		30,6	2					61,2
brmu1	9200-30		30,6	2				61,2	
brmu2	9200-30		30,6	2				61,2	
brmu3	9200-30		30,6	2				61,2	
brmu4	9200-30		30,6	2				61,2	
brmu5	9200-30		30,6	2				61,2	
brmu6	9200-30		30,6	2				61,2	
brm1	8001-50		27,5	2			55,0		
brm2	8001-50		27,5	2			55,0		
brm3	8001-50		27,5	2			251,4		
brsu1	8001-190		125,7	2			251,4		
brmain	DFLP200/32	mit Ergo3 Bremsgrif	91,5	2		183,0			
Fbreak Level					183	251	361	367	734
Wmax Level					183	251	361	367	734