

A5. DESCRIPTIVE OF THE CHARACTERISTICS

A5. 1)FABRIC OF CANOPY

FABRIC CODE	FX40	
SUPPLIER	NAME	TORAY INDUSTRIAL INC
	ADDRESS	NAKANOSHINA 3-CHOME,KITA-KU 530 JAPAN
MATERIAL	POLYESTER	
WEIGHT(GR/SQ.M)	38	
BREAKING STRENGTH (KG/5CM)	WARP	40
	WEFT	30
TEAR STRENGTH (KG/5CM)	WARP	2.2
	WEFT	2.4
WEAVE DESIGN	RIPSTOP	
AIR POROSITY	0-0.01(CC/SEC/C ²)	

A5. 2)SUSPENSION LINE

MATERIAL	ARMIDE YARN WITH NYLON SLEEVE	
SUPPLIER	NAME	ARAMIDE MATSCHAPPIJ VOF(AKJO)
	ADDRESS	VELPERWEG 76, P.O,BOX 9300,6800SB,ARNHEM, NATHERLANDS
DIAMETER(MM)	1.4	
VARN COUNT	1260 DTEX	
NUMBER OF ENDS	4	
BREAKING STRENGTH	130KG	

STÜCKLISTE 2 BLATT

FÜR
F.A.EDER: *John K. S.*

A5. 3) REINFORCING TAPE

FABRIC CODE	T-64500	
SUPPLIER NAME	TEIJIN LIMITED	
ADDRESS	6-7, MINAMIHONMACHI, 1-CHOME, CHOU, OSAKA, JAPAN	
MATERIAL	POLYESTER WITH FILM LAMINATION.	
WEIGHT (GR/SQ.M)	176	
BREAKING STRENGTH (KG/5CM)	WARP	137
	WEFT	118
TEAR STRENGTH (KG/5CM)	WARP	4.2
	WEFT	4.1
WEAVE DESIGN	PLAIN	

A5. 4) RISER

MATERIAL	POLYAMIDE 66 YARN	
SUPPLIER NAME	MONSANTO COMPANY	
ADDRESS	320 INTERSTATE, SUITE 500N, PARKWAY, ATLANTA, GA, 30339, USA	
WEIGHT (GR/SQ.M)	22	
BREAKING STRENGTH	850Kg	
WIDTH (MM)	25	

A5.6) HARDWARE (CARABINER OF RISER)

MATERIAL	STEEL
BREAKING STRENGTH	1300Kg
DIAMETER (MM)	5

FÜR
FA. EDEL: *[Signature]*