

A5. DESCRIPTIVE OF THE CHARACTERISTICS

A5. 1) FABRIC OF CANOPY

Space 24

FABRIC CODE	FX40	
SUPPLIER NAME	TORAY INDUSTRIAL INC	
ADDRESS	NAKANOSHINA 3-CHOME, KITA-KU 530 JAPAN	
MATERIAL	POLYESTER	
WEIGHT (GR/SQ.M)	38	
BREAKING STRENGTH (KG/5CM)	WARP	40
	WEFT	30
TEAR STRENGTH (KG/5CM)	WARP	2.2
	WEFT	2.4
WEAVE DESIGN	RIPSTOP	
AIR POROSITY	0-0.01 (CC/SEC/C ²)	

A5. 2) SUSPENSION LINE

MATERIAL	ARMIDE YARN WITH NYLON SLEEVE	
SUPPLIER NAME	ARAMIDE MATSCHAPPIJ VOF (AKJO)	
ADDRESS	VELPERWEG 76, P.O. BOX 9300, 6800SB, ARNHEM, NETHERLANDS	
DIAMETER (MM)	1.4	
YARN COUNT	1260 DTEX	
NUMBER OF ENDS	4	
BREAKING STRENGTH	130KG	

STÜCKLISTE

2 BLATT

FÜR

FA. EDEL:

H. K. 8

A5. 3) REINFORCING TAPE

FABRIC CODE		T-64500
SUPPLIER	NAME	TEIJIN LIMITED
	ADDRESS	6-7, MINAMIHONMACHI, 1-CHOME, CHOU, OSAKA, JAPAN
MATERIAL		POLYESTER WITH FILM LAMINATION,
WEIGHT (GR/SQ.M)		176
BREAKING STRENGTH (KG/5CM)	WARP	137
	WEFT	118
TEAR STRENGTH (KG/5CM)	WARP	4.2
	WEFT	4.1
WEAVE DESIGN		PLAIN

A5. 4) RISER

MATERIAL		POLYAMIDE 66 YARN
SUPPLIER	NAME	MONSANTO COMPANY
	ADDRESS	320 INTERSTATE, SUITE 500N, PARKWAY, ATLANTA, GA, 30339, USA
WEIGHT (GR/SQ.M)		22
BREAKING STRENGTH		850Kg
WIDTH (MM)		25

A5.6) HARDWARE (CARABINER OF RISER)

MATERIAL	STEEL
BREAKING STRENGTH	1300Kg
DIAMETER (MM)	5