

EINGEGANGEN

STÜCKLISTE

(SPACE 40
TANDEM

05. JUNI 1993

Michael Bethmann

DESCRIPTIVE OF THE CHARACTERISTICS

1) FABRIC OF CANOPY

FABRIC CODE	FX40	
SUPPLIER	NAME	TORAY INDUSTRIAL INC
	ADDRESS	NAKANOSHINA 3-CHOME, KITA-KU 530 JAPAN
MATERIAL	POLYESTER	
WEIGHT (GR/SQ.M)	38	
BREAKING STRENGTH (KG/5CM)	WARP	40
	WEFT	30
TEAR STRENGTH (KG/5CM)	WARP SINGLE	2.2
	WEFT TONG-UE	2.4
WEAVE DESIGN	RIPSTOP	
AIR POROSITY	0-0.01 (CC/SQCM/SEC)	

2) SUSPENSION LINE

MATERIAL	ARMIDE YARN WITH NYLON SLEEVE	
SUPPLIER	NAME	ARAMIDE MATSCHAPPIJ VOF(AKJO)
	ADDRESS	
DIAMETER (MM)	1.4	
YARN COUNT	1260 DTEX	
NUMBER OF ENDS	4	
BREAKING STRENGTH	130Kg	

SPACE 40
TANDEM

3) REINFORCING TYPE

FABRIC CODE		SCRIM W4.20
SUPPLIER	NAME	PORCHER MARINE
	ADDRESS	ROOM 803 SHU LAM BUILDING 23 LUARD ROAD, WANCHAI, HONG KONG
WEIGHT(GR/SQ.M)		180
TEAR STRENGTH (DAN/5CM)	WARP	20
	WEFT	20

4) RISER

MATERIAL		POLYAMIDE 66 YARN
SUPPLIER	NAME	MONSANTO COMPANY
	ADDRESS	320 INTERSTATE, SUITE 500N, PARKWAY, ATLANTA, GA, 30339, USA
WEIGHT(GR/SQ.M)		22
BREAKING STRENGTH		850Kg
WIDTH(MM)		25

5) HARDWARE (CARABINER OF RISER)

MATERIAL	STAINLESS STEEL
BREAKING STRENGTH	1300Kg
DIAMETER(MM)	5