

	Use	Material	Size	Designaion	Manufacturer
1	top surface	Ripstop Nylon	49 gm/sq m	LCN 066 OL KS	Gelvenor
2	bottom surface	Ripstop Nylon	39 gm/sq m soft	9017 E38A	Porcher
	bottom surface	Ripstop Nylon	42 gm/sq m soft	PG3347K	Toray
3	supported ribs	Ripstop Nylon	44 gm/sq m firm	9092 E29A	Porcher
	supported ribs	Ripstop Nylon	42 gm/sq m soft	PG3347K	Toray
4	unsupported ribs	Ripstop Nylon	39 gm/sq m firm	F9017 E29A	Porcher
	unsupported ribs	Ripstop Nylon	42 gm/sq m soft	PG3347K	Toray
5	diagonal ribs	Ripstop Nylon	39 gm/sq m soft	9017 E38A	Porcher
	diagonal ribs	Ripstop Nylon	42 gm/sq m soft	PG3347K	Toray
6	nose reinforcing	Mylar	7 oz		GTS
7	thread	Polyester	V 46		unspecified
8	upper lines	HMA (Kevlar)	80 kg	A-6843-120	Edelrid
9	middle lines	HMA (Kevlar)	120 kg	A-6843-200	Edelrid
10	lower lines	HMA (Kevlar)	180 kg	A-6843-340	Edelrid
11	Shackles	Stainless steel	3.5 mm	Delta	Peguet
12	Riser webbing	Nylon	20mm		Rivori
13	Edging tape	Mylar	25mm		Teijin/Porcher
14	Tab tape	Polyester white	12.5mm		unspecified
15	Tab reinforcing	Sticky Ripstop	44 gm/sq m soft	9092 E38A	Porcher
16	B tab Reinforcing	Dacron white	7oz		unspecified