

SOL PARAGLIDERS *Sol Start One* Materials

Top Wtx40 PU+Silicon Coating

Bottom Wtx40 Pu+Silicon Coating

Profiles/Diagonal Bands Pro-Nyl High Tenacity Nylon rip-stop Hard finish

Lines:

	<u>Stammleine</u>	<i>Stammleine</i>	Stammleine	1. Stockwerk	2.Stockwerk	
Leinenhersteller	COUSIN-FR	COUSIN-FR	COUSIN-FR	COUSIN-FR	COUSIN-FR	
Typenbezeichng	988-2,1	978-1,5	978-1,1	978-1,5	978-1,1	
Nennfestigkeit unverarbeitet	236,8 kg	150 kg	85 kg	150 kg	85 kg	
Durchmesser	2,1 mm	1,5 mm	1,1 mm	1,5 mm	1,1 mm	
Material Kern	Technora	Technora	Technora	Technora	Technora	
Material Mantel	Poliester	Poliester	Poliester	Poliester	Poliester	
DHV Leinenfestigkeit nach 5000 Knickungen	151,1 kg	75,4 kg	36 kg	75,4 kg	36 kg	

Karabiners Ansung Precision 22 mm BI 600 kg

Risers Fitanew 19 x 2,0 mm flat multi BI. 1.600 kg

Pulleys Sol PL14 / FL012A / Ansung Precision

Button Magnetic Italy 15 mm

Reinforcements Nylon 2,8 mm rope (Profile front)

Front/Edges band Multiprint polyester 25 mm grau/grey

Attach Band(loops) Fitanew 10 x 0.8 mm 140 kg

Risers Clips SOL – Raeder

Sewn Tread Guterman / Coats Poliester continuous filament 60 white

Linhanyl / Coats Poliamide 20-30-40 Black