



SOL Sports Ind. e Comércio Ltda.
 Rua Walter Maquardt, 1180
 89259-700 Jaraguá do Sul - SC - Brazil
 Tel : ++55 47 3275 7753
 Fax : ++55 47 3370 7114

SOL PARAGLIDERS **Ellus 5** Materials

Top Wtx40 PU+Silicon Coating 40 gr/sm
 Bottom Wtx40 Pu+Silicon Coating 40 gr/sm
 Profiles/Diagonal Bands Pro-Nyl High Tenacity Nylon rip-stop Hard finish 42 gr/sm

	Stammleine	Stammleine	Stammleine	1. Stockwerk	2. Stockwerk	
Leinenhersteller	COUSIN-FR	PC	PC	PC	PC	
Typenbezeichng	988-2,1	SL-1,5	SL-1,0	SL-1,5 SL-1,0	SL-1,0	
Nennfestigkeit unverarbeitet	236,8 kg	139,3 kg	104,1 kg	139,4 kg 104,1 kg	104,1 kg	
Durchmesser	2,1 mm	1,5 mm	1,0 mm	1,5 mm 1,0 mm	1,0 mm	
Material Kern	Technora	Technora	Technora	Technora	Technora	
Material Mantel	Poliester	Poliester	Poliester	Poliester	Poliester	
DHV/EAPR Leinenfestigkeit nach 5000 Knickungen	151,1 kg DHV	75 kg EAPR	40 kg EAPR	75 kg 40 kg EAPR	40 kg EAPR	

Karabiners Ansung Precision 22 mm BI 800 kg
 Risers Fitanew 15 x 2,0 mm flat multi BI. 1.600 kg
 Pulleys Sol PL14
 Button Magnetic Italy 15 mm
 Reinforcements Nylon Battens (Profile front)
 Front/Edges band Multiprint polyester 25 mm white
 Attach Band(loops) Fitanew 10 x 0.8 mm 140 kg
 Risers Clips SOL – Raeder
 Sewn Tread Guterman / Coats Poliester continuous filament 60 white
 Linhanyl / Coats Poliamide 20-30-40 Black