

## List of material

Rev. 1.2 | 2019-07-03

# Yeti Tandem 3



Description	Article Code	Material	Dimension	Finsih	Manufacturer
Upper sail front	70032 E4G	Polyamid 6.6	32 g/m <sup>2</sup>	Coated, hydrophobic	Porcher Sport
Upper sail rear	70000 E3H	Polyamid 6.6	27 g/m <sup>2</sup>	Coated, hydrophobic	Porcher Sport
Lower sail front	70000 E3H	Polyamid 6.6	27 g/m <sup>2</sup>	Coated, hydrophobic	Porcher Sport
Lower sail rear	70000 E3H	Polyamid 6.6	27 g/m <sup>2</sup>	Coated, hydrophobic	Porcher Sport
Loaded ribs, diagonals, H-Strap bands	70032 E4D / 70000 E91	Polyamid 6.6	32 g/m <sup>2</sup> / 27g/m <sup>2</sup>	Coated, hydrophobic	Porcher Sport
Unloaded ribs, mini ribs	70000 E91	Polyamid 6.6	27 g/m <sup>2</sup>	Coated, hydrophobic	Porcher Sport
Reinforcement	140B HTP opti	Polyester	149 g/m <sup>2</sup>	Coated, Polymer	Dimension Polyant
Rigid rods	-	Plastics	ø 1.6 - 2.5 mm	-	Gin Gliders Inc.
Top lines	8000/U-090   070	Aramid	ø 0.8   0.7 [mm]	UV Protec coating	Edelrid
Middle lines	8000/U-230   190   130   090	Aramid	ø 1.1x1.5   1.2   1.0   0.8 [mm]	UV Protec coating	Edelrid
Main lines	8000/U-360   230   190 TGL 280	Aramid	ø 1.4x1.9   1.1x1.5   1.2 [mm] ø 1.8 [mm]	UV Protec coating Sleeve Polyester	Edelrid Gin Gliders Inc.
Riser (standard)	E362	Dyneema	4 mm	-	Bainbridge
Riser (optional)	70221	Polyester	20 mm	-	Güth & Wolf
Line loop I	Plain Mil-T 5038	Nylon	12 mm	-	Seokwang
Line loop II	Plain Mil-T 5038	Nylon	10 mm	-	Seokwang
Line shackle (standard)	None				
Line shackle (optional)	M300193	Stainless steel	ø 3.85 mm	Stainless	JuTech Korea
Thread for fabric	Mill Faden 150D/3	Polyester bonded	0.05 g	Impregnated	Amann & Söhne
Thread for riser	210D/4	Polyester bonded	0.07 g	-	Wonang
Trailing edge band	140 B HTP Opti	Polyester	15 mm	Coated, Polymer	Dymension Polyant
Binding tape (Leading edge)	Plain Mil-T 5038	Nylon	10 mm	-	Seokwang